





The Alta U47 has a back-illuminated full frame megapixel CCD with exceptionally high quantum efficiency. The standard midband coating (U47-MB) has the highest peak in the visible; the optional broadband coating (U47-BB) has somewhat higher QE in the near UV but lower QE across the visible. The UV-enhanced version (U47-UV) has the highest QE in the UV (See the quantum efficiency curve on page 2.)

Imaging Area of CCD



- 1024 x 1024 array, 13 x 13 micron pixels
- 2 MHz 12-bit and 700 kHz 16-bit digitization
- 32Mbyte camera memory
- USB 2.0 interface: no plug in cards or external controllers
- Programmable, intelligent cooling to 50-55°C below ambient (D02 housing)/ 70-75°C below ambient temperature (D09 housing).
- Binning up to 8 Horizontal x 1024 Vertical
- Subarray readout and fast sequencing modes
- Precision time delayed integration (TDI) and kinetics mode readout
- Programmable fan speed for low / zero vibration
- Two serial port outputs for control of peripheral devices
- General purpose programmable I/O port
- External triggering and strobe controls
- ActiveX drivers included with every system
- Field upgradeable firmware
- Fused silica windows
- Runs from single 12V supply with input voltage monitor
- Compact enclosure

- Astronomy
- Radiology
- Optical testing
- Non-destructive testing



CCD SPECIFICATIONS

CCD	E2V CCD47-10
Array Size (pixels)	1024 x 1024
Pixel Size	13 x 13 microns
Imaging Area	13.3 x 13.3 mm (177 mm ²)
Imaging Diagonal	18.8 mm
Video Imager Size	1.2"
Linear Full Well (typical)	100K electrons
Dynamic Range	83 dB
QE at 400 nm	52% (MB); 75% (BB); 57% (UV)
Peak QE	96% (MB); 86% (BB); 65% (UV)
Anti-blooming	none

For complete CCD specifications, including cosmetic grading, see data sheet from manufacturer.



151 N. Sunrise Ste 902
 Roseville CA 95661 USA
 tel 916 218 7450
 fax 916 218 7451
www.ccd.com




ALTA U47

Camera System Performance

PC Interface	USB 2.0
Max. Cable Length	5 meters between hubs; 5 hubs maximum (max. total of 30m)
Digital Resolution	16 bits at 700 kHz and 12 bits at 2 MHz
System Noise (typical)	9 e ⁻ RMS at 700 kHz and 2 counts at 2 MHz
Pixel Binning	1x1 to 8 x 1024 on-chip
Exposure Time	30 milliseconds to 183 minutes (2.56 microsecond increments)
Image Sequencing	1 to 65535 image sequences under software control
Frame Sizes	Full frame, subframe, focus mode
Cooling (typical)	Thermoelectric cooler with forced air. Maximum cooling 50-55°C below ambient temperature (D02 housing); 70-75°C below ambient temperature (D09 housing).
Dark Current (typical)	0.2 e ⁻ /pixel/sec (-20°C). 0.02 eps for High Cooling D09 housing.
Temperature Stability	± 0.1°C
Camera Head Size	D02. Low profile: D06. Aluminum, hard blue anodized. 6" x 6" x 2.5" (15 x 15 x 6.35 cm) Weight: 3.1 lb. (1.4 kg). Wide Angle: D13. High Cooling: D09 (17.8 x 17.8 x 8.9 cm. 1.9 kg).
Mounting	3.5" bolt circle. 2" 24 tpi thread. Optional Nikon F-mount or Canon FD or EOS/EF mount.
Back Focal Distance	Standard: 1.025" (2.60cm). Low profile: 0.460" (1.17 cm). D09: 1.40" (3.56cm). [optical]
Operating Environment	-22° to 27°C. Relative humidity: 10 to 90% non-condensing.
Cable Length	Standard: 15 ft (4.5m)
Power	40W maximum power with shutter open and cooling maximum. AC/DC "brick" supply with int'l AC input plug (100-240V, 50-60 Hz). Alternate 12V input from user's source.
Shutter	Standard: Melles Griot 43mm. Low profile: no shutter. D09: Melles Griot 63mm.
Remote Triggering	LVTTL input allows exposure to start within 25 microseconds of rising edge of trigger

CCD SENSITIVITY



151 N. Sunrise Ste 902
 Roseville CA 95661 USA
 tel 916 218 7450
 fax 916 218 7451
www.ccd.com